
93 844 48 20
ventas@fenoplastica.com
export@fenoplastica.com
Amadeo Vives,No.8 08440
Cardedeu, Barcelona, Spain



CPV F300 300 S2

SKU: CPV300F30050

Induction fan for CO ventilation and smoke exhaust, series CV. Direct driven centrifugal backward wheel. Galvanized steel coated with RAL. Three-phase engine IP55. Induction fan under Norm EN 12101-3, in F300 (120'). Working service S1 (continuous) (S1) and 300°C for 120 minutes (S2) with an ignition switch function.

© 2021 · FNP Group

93 844 48 20
ventas@fenoplastica.com
export@fenoplastica.com
Amadeo Vives,No.8 08440
Cardedeu, Barcelona, Spain



© 2021 • FNP Group

93 844 48 20
ventas@fenoplastica.com
export@fenoplastica.com
Amadeo Vives,No.8 08440
Cardedeu, Barcelona, Spain

ESPECIFICACIONES TÉCNICAS

Model	CPV F300 300 S2
Motor	Norm motor IP55 0,55 / 2,2 kW 400 / 3 / 50
Thrust	25 / 100 N
Speed	700 / 1.400 rpm.
Air Speed	16,1 / 32,6 m/s
In max	2,2 / 5,6 A
Casing	Steel galvanized / coated in every RAL color
Application	Suitable for temperatures up to 40°C continues and 300°C for 120 minutes (F300). Also ambient execution.

© 2021 · FNP Group