



TWIN BPT BOX 9-9 1.1 KW

SKU: TWBPT90110

Centrifugal fan, with insulated enclosure. With metal multi-bladed double-bladed turbine, driven by belt drive. The BPT BOX is equipped with an adjustable belt tensioning system.

- Multi-blade impeller made of galvanised sheet steel.
 - Double suction with belt drive.
- Enclosure made of galvanised steel sheet with class M1 thermal-acoustic insulation.
 - Motor with IP55 protection and class F insulation.
- S models, sandwich type envelope of 20mm thick rock wool with a density of 70kg/m³. (S)

OPTIONS:

- Air flow: propeller - engine. (MI)
- Different voltages. Frecuencias de 50 o 60Hz
 - 2 speed engines.
- Maximum working temperature of the motor up to 85°C. (T85)
 - Marine engine. (MRM)
 - Motor Agro. (AGM)
 - Painted envelope. (P)
- Cataphoresis protection on the casing and propeller. (KF)

ESPECIFICACIONES TÉCNICAS

Weight	81 kg
FAMILIA	TWIN BPT BOX
TIPOLOGIA	STANDARD APPLICATION
Montaje	Rectangular Duct
Diámetro	09-09mm
Alimentación	~III/50-60Hz
Potencia	1.100 W