

TWIN BPT BOX 9-9 1.5 KW


SKU: TWBPT90150

Centrifugal fan, with insulated enclosure. With metal multi-bladed double-bladed turbine, driven by belt drive. The BPT BOX is equipped with an adjustable belt tensioning system.

- · Multi-blade impeller made of galvanised sheet steel.
 - · Double suction with belt drive.
- Enclosure made of galvanised steel sheet with class M1 thermal-acoustic insulation.
 - · Motor with IP55 protection and class F insulation.
- · S models, sandwich type envelope of 20mm thick rock wool with a density of 70kg/m3. (S)

OPTIONS:

- · Air flow: propeller engine. (MI)
- · Different voltages. Frecuencias de 50 o 60Hz
 - · 2 speed engines.
- · Maximum working temperature of the motor up to 85°C. (T85)
 - · Marine engine. (MRM)
 - · Motor Agro. (AGM)
 - · Painted envelope. (P)
 - · Cataphoresis protection on the casing and propeller. (KF)





Síguenos en Nuestras Redes f ⊙ □ in □ .

ESPECIFICACIONES TÉCNICAS

Weight 78 kg

Fenoplástica NOVO FINT

FAMILIA TWIN BPT BOX

TIPOLOGIA STANDARD APPLICATION

Montaje Rectangular Duct

Diámetro 09-09mm **Alimentación** ~III/50-60Hz

Potencia 1.500 W